



Droppen art nr: 4120-1/4220-1/4221-1/4222-1
Installationsanvisning/Assembly instruction

 Armaturen ska monteras av behörig installatör

Viktigt: Bryt spänningen före installation.

1. Försäkra er om att spänning och frekvens på armaturen och nätet överensstämmer.
2. För att uppnå rätt IP-klass är det viktigt att såväl uppfastningsskruvar som kabel sluter tätt mot bakstycket. Gör därför ett litet kryssjack i gummit, i de hål som ska användas, innan installering.
3. Lossa de två insett-skruvarna (A) och fäst bakstycksplåten i väggen i de två uppfastningshålen (B).
4. Anslut nätledningen till kopplingsplinten via något kabelgenomföringshål (C).
5. Fäst armaturen på bakstycksplåten med insett-skruvarna och brickorna.
6. Montera glaset, fäst med insett-skruvar (D).

Important: Switch off the mains voltage.

Installation:

1. Ensure that voltage and Hz on the fixture and mains voltage are the same.
2. Its important that screws and cable are fitted tightly to the fixture to obtain the IP rating
3. Loosen the screws (A) and fix the wall plate through the wholes (B).
4. Connect the cable to the terminal block through the whole C.
5. Fix the fitting to the plate with the screws.
6. Mount the glass, fix with the screws (D).

